

# STYLE REF: PM4002

## STYLE NAME: JACKSON



# Rock Fall®

INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 SRC | UK 3-16 (WHOLE SIZES) | COLOUR: BLACK

PROTECTIVE TOECAP AND MIDSOLE, JACKSON IS LIGHTWEIGHT AND DEVELOPED WITH PREMIUM MATERIALS INCLUDING AN ACTIV-STEP® SHOCK ABSORBING DUAL DENSITY PU OUTSOLE.

# PM4002



### Upper Material

Water repellent smooth black leather

### Protective Components

Protective steel toecap and stainless steel anti-penetration midsole

### Lining Materials

Moisture wicking breathable mesh fabric lining

### Scuff Cap and Outsole

Activ-Step® shock absorbing PU outsole

### Footbed

Anti-fatigue EVA footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/03/2018

[WWW.ROCKFALL.COM](http://WWW.ROCKFALL.COM) | [WWW.ROCKFALL.COM/PRODUCTS/PM4002](http://WWW.ROCKFALL.COM/PRODUCTS/PM4002)

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

**EC DECLARATION OF CONFORMITY**



**Head Office & Distribution Centre**

Rock Fall UK Limited  
Unit 1 Major House  
Wimsey Way  
Alfreton, Derbyshire  
England. DE55 4LS

**E:** sales@rockfall.co.uk  
**T:** 01773 608616

[www.rockfall.co.uk](http://www.rockfall.co.uk)

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Declares that the PPE described hereafter;

**PRO-MAN PM4002**

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00331260** Issued by:-

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**

Signature:

Position: Director

Date: 01/01/2017



# EC Type Examination Certificate



### Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.  
Centre Court  
Meridian Business Park  
Leicester, LE19 1WD  
United Kingdom  
Phone: +44 (0)116 263 0330  
Fax: +44 (0)116 263 0311



www.intertek.com

<b>Issued to</b>	: Rock Fall UK Ltd Major House, Unit 1 Wimsey Way, Alfreton, Derbyshire, United Kingdom DE55 4LS	
<b>Authorised Representative</b>		
<b>Manufacturer</b>		
<b>Date of Issue</b>	: 18 May 2013	
<b>Expiry Date</b>	: 18 May 2018	
<b>Certificate No.</b>	: LEC FI00331260	
<b>Product Reference(s)</b>	: 4002/S3, 4003/S3, 4004/S3, 107 (TC310)/S3, 109B/S3, 109C/S3, 104/S3	
<b>Description</b>	: Construction	: PU/PU Double Density Injection
	: Toecap	: Steel Toecap
	: Midsole	: Steel Plate
	: Last	: 604
	: Sole	: PU/PU Injection
	: Mould	: 2010
	: Test Report(s)	: See Technical File
	: Size Range	: 36 – 51
	: Category	: S3 SRC

*M. [Signature]*  
Assessor

18/05/2013  
Date

*P. Williams*  
Certification Manager

18/05/2013  
Date

For and on behalf of **ITS Testing Services (UK) Limited**

Registered in England No. 1408264 Registered Office: 25 Savile Road, London W1S 2ES

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



TEST REPORT

Number: GZHT90166117

Tests Conducted (As Requested By The Applicant)

7 Internal Length Of Toe Cap (Toe Protection) (BS EN ISO20344: 2004 /A1:2007(5.3)):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	Left:	42 mm	Min. 40 mm	Pass
	Right:	42 mm	Min. 40 mm	Pass

Expanded Uncertainty: 0.89 mm, with k= 2.22 at 95% confidence level

8 Impact Resistance (Toe Protection) (BS EN ISO20344: 2004 /A1:2007(5.4)):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	Left:	16.0 mm	Min. 14.5 mm (#)	Pass
	Right:	16.0 mm	Min. 14.5 mm (#)	Pass

Remark: # =In Addition, The Toecap Shall Not Develop Any Cracks On The Test Axis Which Go Through The Material, ie. Through Which Light Can Be Seen.

Expanded Uncertainty: 0.49(Urel), with k= 1.96 at 95% confidence level

9 Compression Resistance (Toe Protection) BS EN ISO20344: 2004 /A1:2007(5.5):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	Left:	16.5 mm	Min. 14.5 mm	Pass
	Right:	17.0 mm	Min. 14.5 mm	Pass

Expanded Uncertainty: 0.13(Urel), with k= 1.96 at 95% confidence level

10 Outsole Slip Resistance (BS EN ISO 20344:2004/A1:2007 (5.18), SRC, 23 °C):

<u>Size 43</u>			<u>Requirement</u>	<u>Pass/Fail</u>
	<u>Ceramic Tile/Sodium Lauryl Sulphate</u>			
	Heel Part	0.45	Min. 0.28	Pass
	Flat Contact	0.47	Min. 0.32	Pass
	<u>Steel Floor/Glycerol</u>			
	Heel Part	0.17	Min. 0.13	Pass
	Flat Contact	0.20	Min. 0.18	Pass